SLX-VIDEO

EDGE VIDEO RECORDING HARDWARE SPECIFICATIONS



| CAMERA SPECIFICAT | TIONS | | |
|--------------------|-------------|--|--|
| Lens | 1080P | 110° fixed lens diagonal field of view | |
| | 4K | 124° fixed lens diagonal field of view | |
| Wide Dynamic Range | 1080P 4K | 72 dB at 8x gain 73.5 dB at 8x gain | |

| COMPRESSION STANDARD | | |
|----------------------|-------|--------------------------|
| Video Compression | | H.264 |
| H.264 Type | | High Profile |
| Video Bit Rate | 1080P | Default 1mb/s |
| Video bit Rate | 4K | Default 4mb/s |
| Dual Streams | | Supported for 1080p only |

| IMAGE | | |
|------------------|-------|--|
| Max. Resolution | 1080P | 1920 x 1080 pixels |
| Max. Resolution | 4K | 3840 x 2160 pixels |
| Max Frame Rate | | 30 fps |
| On-Board Storage | | Built-In Micro SD/SDHC/SDXC Slot, Up to 1.5 TB |

| ELECTRICAL/MECHANICAL/ ENVIRONMENTAL | |
|--------------------------------------|---|
| Electrical Input | See SLX-Controller Spec Sheet for more information.B870 rated 120-480V, B671 rated 220-240V.ANSI C136.10 and C136.41 compliant. |
| Power Consumption | 4W Avg @120V, 5.75W Max @120V |
| Vandal Resistance | IK-08 rated. |
| Ingress Protection | IP-66 rated |
| Temperature Rating | -30°C to +40°C rated (-22°F to +104°C) |
| Total Dimensions | 88 mm maximum diameters, 216 mm maximum height |
| Total Weight | 900 g |

| ONVIF | |
|----------------------------|-----|
| Profile S (Streaming) | Yes |
| Profile G (Edge Recording) | Yes |

| CERTIFICATIONS | |
|-------------------------------|----------------|
| Product Safety Certification | UL |
| FCC | FCC, IC |
| Cellular module certification | PTCRB, FCC, IC |

| PRIVACY | | |
|---------------------------|---|--|
| Privacy | The system allows for Privacy Masking | |
| License Plate Recognition | The system does not recognize or record license plates | |
| Facial Recognition | The system does not track individuals or perform any form of facial recognition | |
| Audio Recording | The system is not equipped with a microphone for audio recording | |

| NETWORK | |
|---------------|-----|
| Communication | LTE |

All information provided is subject to change without notice.



MILESTONE

SOFTWARE SPECIFICATIONS



USER INTERFACE

Smart Client with intuitive, user-friendly interface

Simple access to live streaming and edge retrieval functionality with separate, easy-to-navigate tabs

One-click access to live-streaming (1 minute streaming default to limit cellular data usage)

User friendly calendar based access to edge-retrieval and video export functionality

Create custom views for multi-camera viewing

ASSET MANAGEMENT

Liveable Cities cameras come pre-commissioned to Milestone

Device Firmware upgrades available over-the-air

INTEROPERABILITY STANDARDS

ONVIF Profile G (edge recording uploads) supported

ONVIF Profile S (streaming) supported

VIDEO STORAGE

Cloud based video storage, no on-premise storage requirements

30-day cloud storage of edge retrieved video

Video can be exported in .mkv file format

Live stream video is not automatically saved into cloud storage

UPGRADES AVAILABLE

Greater than 30-day cloud storage of edge retrieved video

Grouping of devices by region

Evidence Locker

Web Client provides one-click access to live-streaming and access to view videos which have been retrieved by Smart Client

All information provided is subject to change without notice.



ORDER GUIDE

| REPEAT ORDER |
|--------------|
| □YES □NO |

^{*}Recommended for 4K Camera

| | | Repeat orders require only grey-outlined shaded sections filled | | |
|--|--|--|--|--|
| ORDERING AND SETUP INFORMATION | | | | |
| Order Configuration | | Example Configurations | | |
| | | CX-2-A-512-05-M-VC | | |
| Quantity Required | | Comments | | |
| Customer Name | | Project Name | | |
| Approved By | | Date | | |
| Customer ID# (Internal - field) Enable Streetlighting Data Collection, Visualization, And Control | | | | |
| | | YES Streetlighting LED HPS Induction Dimming type 0-10V DALI None | | |
| NTACT INFORMATION | | | | |
| tomer Name: | | State/Province: | | |
| ephone: | | Country: | | |
| ddress: | | Postal Code/ Zip Code: | | |
| <i>'</i> : | | | | |
| min User* | | | | |
| ame Phone | | Email | | |
| ANDARD USER 1 | | | | |
| ame Phone | | Email | | |
| ANDARD USER 2 | | | | |
| Phone | | Email | | |

^{*}Admin User has the ability to direct liveable cities to add and remove users, and will be the point of contact for the customer for communications around product support, firmware upgrades, etc



^{** 0.6}GB data used by camera in steady state to communicate on-line status and health with VMS $\,$